

SUBMERSIBLE VERTICAL ELECTRIC PUMPS



**APPLICATIONS**

- Pumping of coolants, lubricants and condensate.
- Machine tools, welders, engine test stands.
- Cooling systems.
- Washing systems.
- Boosters.
- Fire-fighting systems.

**SPECIFICATIONS**

PUMP

- **Delivery:** up to **72 m<sup>3</sup>/h.**
- **Head:** up to **247 m.**
- **Liquid temperature:**  
-10°C to +90°C for "S" and "N" versions with coupling,  
-10°C to +60°C for close-coupled "E" versions.
- Maximum ambient temperature: +40°C.
- Tested in compliance with ISO 2548 for class C standard pumps.
- Rotation direction: clockwise when looking at pump end (indicated by the arrow on adapter and coupling).
- **Mechanical seal** in compliance with **DIN 24960 and ISO3069** for "S" and "N" versions, GOULDS PUMPS seal for "E" versions. Standard mechanical seal used for clean liquids. For applications with contaminated liquids there are available seals in Tungsten/Silicon/FPM or Tungsten Carbide/Silicon/FPM or Silicon/Silicon/FPM.

- Tank coupling flange in compliance with DIN 5440 and EN 12157.
- Standard installation in vertical position: however, all models (except the GSVI30 and 60 versions with over 5 stages at 50 Hz, and with over 4 stages at 60 Hz) can be installed horizontally.
- Reduced axial thrust allows standard motors to be used (for "S" and "N" versions).
- These pumps can handle clean liquids free of abrasives substances or fibres, with kinematic viscosities up to 37mm<sup>2</sup>/sec., with suitably sized motor.
- Minimum level of suction liquid: 25mm for GSVI 2-4-6-8-16 models and 100 mm for GSVI 30 and 60 models.
- Suction base has filter with 2 mm. diameter holes (GSVI2-4) or 3 mm. holes (GSVI 8-16-30-60).
- AISI 316 STAINLESS STEEL "N" version available for models GSVI 2-4-8-16.
- Longer pump columns (from coupling flange to suction base) are available on request. Possible variants follow the number of upperstages indicated in each model's dimensions table.

MOTOR

- Squirrel cage, finned aluminium casing, enclosed construction with external ventilation.
- **IP55 protection.**
- **Class F insulation.**
- Performance in compliance with CEI 2-3 (IEC 34,1).
- **Construction design:**  
- Close-coupled for "E" version (GOULDS PUMPS motor);  
- Standard motor for "S" and "N" V18 versions, for power up to 4 kW, and V1 versions for power above 4 kW.
- **Standard voltage:**  
**Single-phase** 220-240V - 50 Hz on request.  
**Three-phase** 220-240/380-415 V - 50 Hz with power up to 3 kW;  
up above 23 kW  
380-415 V - 50 Hz with power